

## Technical Specification

Sr. No.	PROPERTY	International Std. ISO 13006/EN 176 Group Bla	COLORTILE VALUE
1.	Deviation in Length	± 0.5%	± 0.4%
2.	Deviation in Thickness	± 5%	± 3%
3.	Straightness of Sides	±0.5%	±0.5%
4.	Rectangularity	±0.6%	±0.4%
5.	Surface Flatness	±0.5%	±0.2%
6.	Water absorption	±3.6%	±3.6%
7.	Bending Strength	≥220kgs/cm <sup>2</sup>	≥270kgs/cm <sup>2</sup>
8.	Chemical Resistance	Resistance to all alkalis (except Hydro flouric acid and its compounds)	Resistance to all alkalis (except Hydro flouric acid and its compounds)
9.	Thermal Shock	10 cycles	10 cycles

## Packing Detail

Size	Thickness	No. of Tiles/Box	Coverage Area	Wt. of Box
300x900mm	10.7 mm (Approx.)	4 pcs.	1.08 sq. mt.	20.0 kgs. (Approx.)
300x600mm	9.8 mm (Approx.)	8 pcs.	1.44 sq. mt.	24.0 kgs. (Approx.)
300x300mm	8.5 mm (Approx.)	9 pcs.	0.81 sq. mt.	11.2 kgs. (Approx.)